# Author Index


| | | |
|---|---|---|
| Aglietti, G. S. | Development of the MiniSIL™ structural design | 255–263 |
| Aglietti, G. S. | SIL SGS-2.4 S-band ground station | 265–272 |
| Allen, C. B. | The effect of grid topology and density on inviscid hovering rotor solutions | 81–95 |
| Anandakumar, K. | Statistical discrete gust analysis of tower-based atmospheric turbulence data for aircraft response studies | 143–162 |
| Ananthkrishnan, N. | Transient resonance of rolling finned projectiles | 97–103 |
| Barret, R. V. | The use of suction to suppress disturbances in laminar flow caused by insect and other surface debris | 277–292 |
| Barrington-Brown, A. J. | Development of the MiniSIL™ structural design | 255–263 |
| Barrington-Brown, A. J. | SIL SGS-2.4 S-band ground station | 265–272 |
| Behrouzi, P. | Computational fluid dynamics prediction of intake ingestion relevant to short take-off and vertical landing aircraft | 131–142 |
| Bowden, R. | Automated visual inspection of dry carbon-fibre reinforced composite preforms | 377–386 |
| Butcher, M. R. | Spacecraft thermal design: particular problems with small satellites | 245–253 |
| Cao, Z. | Dynamic behaviour of open-loop systems of intelligent structures | 293–303 |
| Chen, S. | Dynamic behaviour of open-loop systems of intelligent structures | 293–303 |
| Creasey, R. | Small satellite projects in the European Space Agency (ESA) | 201–212 |
| Cuerno-Rejado, C. | Historical rotorcraft restoration: the C-30 Autogiro | 71–80 |
| Davis, R. I. | Robotic tacking of high-quality composite preforms | 173–185 |
| De Pasquale, E. | A non-linear adaptive guidance algorithm for last-stage launcher control | 45–55 |
| Dewing, A. | Robotic tacking of high-quality composite preforms | 173–185 |
| Eastham, J. | Robotic tacking of high-quality composite preforms | 173–185 |
| Ellenrieder, T. J. | The modelling and validation of the vertical dynamics of a hot air ballon | 57–62 |
| Eustace, R. | The use of suction to suppress disturbances in laminar flow caused by insect and other surface debris | 277–292 |
| Fossa, M. | Liquid sheet radiators for space power systems | 399–406 |
| Garcia-Julia, E. | A universal dimensionless model for the MacCready sailplane theory | 105–115 |
| Gómez-Tierno, M. A. | A universal dimensionless model for the MacCready sailplane theory | 105–115 |
| Henderson, J. F. | The dynamics of an airborne towed target system with active control | 305–319 |
| Hernández, J. A. | Essentially non-oscillatory schemes for the Euler equations on unstructured meshes | 1–12 |
| Hodson, H. P. | A study of unsteady wake-induced boundary-layer transition with thermochromic liquid crystals | 163–171 |
| Ireland, B. | The dynamics of an airborne towed target system with active control | 305–319 |
| Ireland, P. T. | A study of unsteady wake-induced boundary-layer transition with thermochromic liquid crystals | 163–171 |
| Jesson, J. R. | Life assessment of a critical aeroengine part using finite element crack modelling | 117–124 |
| Kailas, S. V. | Statistical discrete gust analysis of tower-based atmospheric turbulence data for aircraft response studies | 143–162 |
| Kam, T. Y. | Failure analysis of a frangible laminated composite canister cover | 187–195 |
| Karnezis, P. | Life assessment of a critical aeroengine part using finite element crack modelling | 117–124 |
| Katti, R. A. | Thermal sensitivity analysis of a 22 N bipropellant thruster in a spacecraft | 321–335 |
| Kim, D. | Optimal sensor location for robust fault detection filter | 13–21 |
| Kim, H. D. | Mass-averaging pseudo-shock model in a straight flow passage | 365–375 |
| Kim, Y. | Optimal sensor location for robust fault detection filter | 13–21 |
| Kittichaikan, C. | A study of unsteady wake-induced boundary-layer transition with thermochromic liquid crystals | 163–171 |
| Krishnan, S. | Effect of motor length and propellant formulation on nozzleless solid rocket performance | 35–44 |
| Lawrence, T. | Low-cost orbit manoeuvres for minisatellites using novel resistojet thrusters | 223–231 |
| Leduc, J. | Low-cost orbit manoeuvres for minisatellites using novel resistojet thrusters | 223–231 |
| López-Díez, J. | Historical rotorcraft restoration: the C-30 Autogiro | 71–80 |
| López-Ruiz, J. L. | Historical rotorcraft restoration: the C-30 Autogiro | 71–80 |
| Luke, P. | A study of churning losses in dip-lubricated spur gears | 337–346 |
| Lyshevski, S. E. | State-space multivariable non-linear identification and control of aircraft | 387–397 |
| McGuirk, J. J. | Computational fluid dynamics prediction of intake ingestion relevant to short take-off and vertical landing aircraft | 131–142 |
| Martínez-García, J. J. | A universal dimensionless model for the MacCready sailplane theory | 105–115 |
| Matsuo, K. | Mass-averaging pseudo-shock model in a straight flow passage | 365–375 |
| Mitchell, T. A. | Robotic tacking of high-quality composite preforms | 173–185 |


© IMechE 1999

| | | |
|---|---|---|
| Mitchell, T. A. | Automated visual inspection of dry carbon-fibre reinforced composite preforms | 377–386 |
| Miyazato, Y. | Mass-averaging pseudo-shock model in a straight flow passage | 365–375 |
| Newman, S. | The phenomenon of helicopter rotor blade sailing | 347–363 |
| Olver, A. V. | A study of churning losses in dip-lubricated spur gears | 337–346 |
| Parker, S. C. J. | A novel shearography system for aerospace non-destructive testing | 23–33 |
| Potjewyd, J. | The dynamics of an airborne towed target system with active control | 305–319 |
| Pradeep, S. | Transient resonance of rolling finned projectiles | 97–103 |
| Raisinghani, S. C. | Transient resonance of rolling finned projectiles | 97–103 |
| Ramakrishnan, R. | Effect of motor length and propellant formulation on nozzleless solid rocket performance | 35–44 |
| Salter, P. L. | A novel shearography system for aerospace non-destructive testing | 23–33 |
| Sarhadi, M. | Robotic tacking of high-quality composite preforms | 173–185 |
| Sarhadi, M. | Automated visual inspection of dry carbon-fibre reinforced composite preforms | 377–386 |
| Suresha, S. | Thermal sensitivity analysis of a 22 N bipropellant thruster in a spacecraft | 321–335 |
| Sweeting, M. N. | Low-cost orbit manoeuvres for minisatellites using novel resistojet thrusters | 223–231 |
| Tagliafico, L. A. | Liquid sheet radiators for space power systems | 399–406 |
| Teofilatto, P. | A non-linear adaptive guidance algorithm for last-stage launcher control | 45–55 |
| Turner, R. F. | Small spacecraft missions—the US scene | 213–221 |
| Wang, W. T. | Failure analysis of a frangible laminated composite canister cover | 187–195 |
| Wells, N. S. | Development of the STRV 1c and 1d mission based on the experiences of STRV 1a and 1b | 233–243 |
| Wen, B. | Dynamic behaviour of open-loop systems of intelligent structures | 293–303 |
| Whitcomb, G. P. | Small satellite projects in the European Space Agency (ESA) | 201–212 |
| Wicks, A. | Development of the MiniSIL™ structural design | 255–263 |
| Wicks, A. | SIL SGS-2.4 S-band ground station | 265–272 |
| Wu, J. H. | Failure analysis of a frangible laminated composite canister cover | 187–195 |
| Zamecnik, M. | Essentially non-oscillatory schemes for the Euler equations on unstructured meshes | 1–12 |
| Zhong, S. | A study of unsteady wake-induced boundary-layer transition with thermochromic liquid crystals | 163–171 |




© IMechE 1999